



## MATERIAL SAFETY DATA SHEET (MSDS)

Company Identification:

**Miner Elastomer Products Corporation  
1200 East State Street  
Geneva, IL 60134  
630.232.3000**

### TECSPAK MATERIAL SPECIFICATION:

EPCTEEEA  
EPCTEEEB  
EPCTEEEC  
EPCTEEED  
EPCTEEEE  
EPCTEEEF

## HAZARDS IDENTIFICATION

### Product hazard category

Combustible dust

### Label content

Pictogram	: not required
Single word	: Warning
Hazardous warnings	: May form combustible dust concentrations in air
Hazardous prevention Measures	: not required

### Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

## COMPOSITION / INFORMATION ON INGREDIENTS

This product does not contain any components that require disclosure according to OSHA Hazard Communication Standard 2012

## FIRST AID MEASURES

General advice	: No applicable data available
Inhalation	: Move to fresh air in case of accidental inhalation of fumes from overheating or combustion. If not breathing give artificial respiration. If breathing is difficult, give oxygen. Call a physician.
Skin contact	: The compound is not likely to be hazardous by skin contact, but cleaning the skin after use is advisable. Cool skin rapidly with cold water after contact with molten material. Do not peel polymer from the skin. Obtain medical treatment for thermal burn.
Eye contact	: In case of contact, immediately flush eyes with plenty of water or at least 15 minutes. Call a physician.
Ingestion	: No specific intervention is indicated. Consult a physician if necessary.
Most important	: No applicable data available.

symptoms/effects, acute  
and delayed

Protection of first-aiders : No applicable data available.

Notes to physician : No applicable data available.

## **FIRE FIGHTING MEASURES**

Suitable extinguishing media : Water, Foam, Dry Chemical, Carbon dioxide (CO<sub>2</sub>)

Unsuitable extinguishing  
media : No applicable data available.

Specific hazards : Combustible. Large molten masses may ignite spontaneously in air. Water quenching is good practice. Minimize the generation and accumulation of dust. Failure or malfunction of temperature control systems on processing equipment, such as extruders, may create explosion hazards. Hazardous combustion products may include: (see also section 10) Carbon monoxide, Carbon dioxide.

Special protective  
equipment for firefighters : Wear self-contained breathing apparatus and protective suit.

Further information : Evacuate Personnel and keep upwind of fire.

## **ACCIDENTAL RELEASE MEASURES**

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Safeguards (Personnel) : Spilled material is a slipping hazard.

Environmental precautions : Do not discharge to streams, ponds, lakes or sewers.

Spill Cleanup : Spills of fine material should be cleaned using gentle sweeping or vacuuming. Cleaning methods (e.g. compressed air) which can generate potentially combustible dust clouds should not be used. Dust deposits should not be allowed to accumulate on surfaces, as these may form explosive mixture if they are released into the atmosphere in sufficient concentration. Use only non-sparking tools.

Accidental Release Measures : No applicable data available.

## HANDLING AND STORAGE

Handling (Personnel)	: Open container only in well-ventilated area. Wash hands thoroughly after handling. Provide appropriate ventilation at dryers, machinery and at places where dust or volatiles can be generated. Do not breathe dust. Pneumatic conveying and other mechanical handling operations can generate combustible dust. Minimize the generation and accumulation of dust. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces.
Handling (physical Aspects)	: No applicable data available.
Dust explosion class	: No applicable data available.
Storage	: Store in cool, dry place. Keep container closed to prevent contamination. Keep in an area equipped with sprinklers.
Storage period	: No applicable data available.
Storage temperature	: No applicable data available.

## EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls	: General mechanical ventilation is normally adequate but use local exhaust where necessary to maintain exposures below acceptable limits. Use local exhaust to completely remove vapors and fumes liberated during hot processing from the work area.
Personal protective equipment	
Respiratory protection	: Additives in this product do not present a respiration hazard unless the product is ground to a powder of respirable size and the dusts are inhaled. All dusts are potentially injurious to the respiratory tract if respirable particles are generated and inhaled. A respiratory protection program that meets country requirements must be followed whenever workplace conditions warrant respirator use. Consult the respirator manufacture to determine appropriate type of equipment for given application. Observe respirator use limitations specified by the manufacturer. Consult the OSHA respiratory protection information located at 29CFR 1910.134. Use a positive pressure air supplied respirator if exposure levels are not known or there are any other circumstances where air purifying respirators may not provide adequate protection.

Hand protection : Additional protection: Wear leather or cotton gloves when grinding, sawing, routing, drilling or sanding. When handling hot material, use heat resistant gloves.

Eye protection : Wear safety glasses with side shields. Wear tightly fitting chemical splash goggles and face shield when possibility exists for eye and face contact due to splattering or splashing of molten material. A full-face mask respirator provides protection from eye irritation.

Skin and body protection : If there is a potential for contact with hot/molten material wear heat resistant clothing and footwear.

Exposure Guidelines  
Exposure Limit Values

This product does not contain any exposure limits that require disclosure according to OSHA Hazard Communication Standard 2012.

Non-Constituent(s)

Dust (inhalable and respirable fraction)			
Permissible Exposure limit:	(OSHA)	5mg/m3	8hr. TWA Respirable fraction.
Permissible Exposure limit:	(OSHA)	15mg/m3	8hr. TWA Total dust.
TLV	(ACGIH)	3mg/m3	TWA Respirable particles.
TLV	(ACGIH)	10mg/m3	TWA Inhalable particles.

## PHYSICAL AND CHEMICAL PROPERTIES

Appearance  
Physical state : Solid  
Form : Pellets  
Color : Natural

Odor : None

Odor threshold : Not applicable

pH : Not applicable

Melting point/freezing point	: Melting point/range : > 130 °C (> 266 °F)
Boiling point/boiling range	: Boiling point/boiling range : Not applicable
Flash point	: Not applicable
Evaporation rate	: Not applicable
Flammability (solid, gas)	: May form combustible dust concentrations in air.
Upper explosion limit	: Not applicable
Lower explosion limit	: Not applicable
Vapor pressure	: Not applicable
Vapor density	: Not applicable
Specific gravity (Relative density)	: >1
Water solubility	: Insoluble
Solubility(ies)	: No applicable data available.
Partition coefficient: n-octanol/water	: No applicable data available.
Auto-ignition temperature	: Not applicable
Decomposition temperature	: > 275°C Thermal decomposition of resin accelerates above temperature listed. Decomposition can occur below the recommended processing temperature limit. Decomposition is a function of both processing temperature and time at that temperature.
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: Not applicable

## STABILITY AND REACTIVITY

Reactivity	: Stable at normal ambient temperature and pressure.
Chemical stability	: Stable at normal ambient temperature and pressure.
Possibility of hazardous reactions	: Polymerization will not occur.
Conditions to avoid	: Temperature > 275 °C (> 527 °F) Abnormally long processing time or high temperatures can produce irritating and toxic fumes. Decomposes on heating. At temperatures above the “conditions to avoid” temperature, thermal decomposition of the resin accelerates. Decomposition can occur below the recommended processing temperature limit. Decomposition is a function of both processing temperature and time at that temperature.
Incompatible materials	: Strong acids strong bases, Strong oxidizing agents
Hazardous decomposition	: Hazardous thermal decomposition products may include: Tetrahydrofuran, Carbon dioxide, Carbon monoxide, 2-Methylpropene, Acetaldehyde, Acrolein, Propionaldehyde, Acetic acid, Formic acid.

## TOXICOLOGICAL INFORMATION

TecsPak thermoplastic polyester elastomer Further information	: No data is available on the product itself. For additional toxicity data, write to:
--	---

Miner Elastomer Products Corporation  
1200 East State Street  
Geneva, IL 60134  
630.232.3000

### Carcinogenicity

The carcinogenicity classifications for this product and/or its ingredients have been determined according to HazCom 2012, Appendix A.6. The classifications may differ from those listed in the National Toxicology Program (NTP) Report on Carcinogen in the international Agency for Research on Cancer (IARC) Monographs (latest edition).

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA, or ACGIH as a carcinogen.

## ECOLOGICAL INFORMATION

Additional ecological information : No data is available on the product itself. Toxicity is expected to be low based on insolubility in water.

## DISPOSAL CONSIDERATIONS

Waste disposal methods : Preferred options for disposal are:  
Product Recycling or incineration with energy recovery.  
The high fuel value of this product makes incineration very desirable for material that cannot be recycled.  
Treatment, storage, transportation, and disposal must be in accordance with applicable federal, state/provincial, and local regulations.

Contaminated packaging : No applicable data available.

## TRANSPORTATION INFORMATION

Not classified as dangerous in the meaning of transport regulations.

## REGULATORY INFORMATION

TSCA : In compliance with TSCA Inventory requirements for commercial purposes.

SARA 313 Regulated Chemical(s) : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, section 313.

PA Right to Know : Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for special hazardous substances): None known.

NJ Right to Know Regulated Chemical(s) : Substances on the New Jersey Workplace Hazardous Substances List present at a concentration of 1% or more (0.01% for substances identified as carcinogens, mutagens or teratogens): None known.



For : EPCTEEEA, EPCTEEEB, EPCTEEEC, EPCTEEED, EPCTEEEE, EPCTEEEF

California Prop. 65 : Chemicals known to the state of California to cause cancer,  
birth defects or other harm: none known

For : EPCTEEEA-1, EPCTEEEB-1, EPCTEEEC-1, EPCTEEED-1, EPCTEEEE-1,  
EPCTEEEF-1

Modified for U.V. Protection.

California Prop. 65 : WARNING! This product contains chemicals known to the state  
of California to cause cancer